City of Sunnyvale 2006 Bicycle Plan



Appendices A-F



Contents

ppendix A: Toolkit of Bikeway ImprovementsA	-1
A.1 Bicycle accommodation dimensions A	
A.2 Restriping A	3
Restriping without travel lane removal A	-3
Travel lane removal A	3
A.3 Parking modifications A	
A.4 Widening A	
A.5 Shared Roadway Bicycle Marking A	5
A.6 Speed Management A	
Overview A	
Sunnyvale's Neighborhood Traffic Calming Program A	
Bicycle Boulevards A	
ppendix B : Municipal Code Sections Relevant to Bicycling B	
B.1 Title 10: Vehicles and Traffic B	; - 1
D.2 11.10 10: 20111119	3-4
Appendix C: Standard Operating Procedure: Bicycle and Pedestrian Safety	
Through Work ZonesC	-1
Appendix D : MTC 2004 SafetyTAP Study Excerpt: Bicycle-Related CollisionsD	-1
ppendix E : Sample Visual Guide to Bicycle Racks E	
Appendix F : Reference information used in developing this Plan F	



List of Tables

Table A.1: Toolkit of roadway improvement options	B-1
Table B.2: Municipal Code – Chapter 19 (Zoning) sections relating to bicycling	
Table F.1: City of Sunnyvale documents reviewed	
Table F.2: Other documents reviewed	
Table F.3: Agencies and firms contacted	.F-2
List of Figures	
Figure A.1: Typical Bicycle Lane Section – With and Without Parking	A-2
Figure A.2: Typical Bicycle Route Section (Wide Outside Lanes)	A-2
Figure A.3: Adding bike lanes with a "4 to 3 conversion"	A-3
Figure A.4: Parking modification options for adding bike lanes	A-4
Figure A.5: Shared Roadway Bicycle Marking	A-6
Figure A.7: Lateral placement of marking	A-6
Figure A.6: Marking in use	A-6
Figure A.8: Sunnyvale "Share The Road" sign (from 2000 Bicycle CIP)	A-6
Figure A.9: MUTCD "Share The Road" sign assembly	A-6
Figure A.10: Experimental regulatory sign for narrow-lane situations	
Figure A.11: Neighborhood traffic calming devices in Sunnyvale	
Figure A.12: Motor vehicle through-restrictions on Palo Alto's Bryant Bike Boulevard.	
Figure C.1: Standard Operating Procedure for Right Lane and Bike Lane Closures	
Figure E.1: Acceptable Bicycle Rack Types	
Figure E.2: Unacceptable Bicycle Rack Types	





Appendix A: Toolkit of Bikeway Improvements

The 2000 Bicycle Capital Improvement (CIP) study defined a toolkit of bicycle facility improvement types and identified the most likely type for each roadway segment in the City. Sunnyvale's 2006 Bicycle Transportation Plan updates this toolkit by adding:

- A "parking pockets" variation of minor widening
- A "Speed Management" option
 (for low volume residential collector streets where parking removal or
 substandard-width striped bicycle-and-parking lanes were previously
 recommended)
- A "Bicycle Boulevard" enhancement of speed management

Table A.1 lists the options in the updated toolkit:

Table A.1: Toolkit of roadway improvement options

Tools for adding bike lanes

Bike Plan Figure

1	Re-striping (without parking re			
	a) Without travel lane removal		5.1	
	b) Removal of a travel lane, and possible addition of a center turn lane where none existed	Considered where vehicles per lane per peak hour is sufficiently low. Adding a center-turn lane creates opportunities for median refuges that improve pedestrian crossing safety.	5.2	
2	Parking modifications			
	a) Parking removal, both sides	Choice depends on land use (residential or commercial), occupancy, turnover, and time-of-	5.3	
	b) Parking removal, one side	day patterns, and the availability of off-street or		
	c) Time-restricted parking	side-street parking		
3	Widening			
	a) Parking pockets	Where a landscape strip is present, creating indentations for parking to avoid widening entire blocks	5.6	
	b) Minor widening	Not requiring utility relocation or property acquisition	5.0	
	c) Major widening	Requiring utility relocation or property acquisition		

Tools for streets without bike lanes

100	10015 101 Streets without pike lanes		
4	Shared Lane Marking	Considered where bike lanes are desirable but lane removal, parking modifications and widening are impractical	5.4
5	Speed management	For low-volume residential streets where cyclists can be passed using the full street width	
	a) Without traffic control changes		5.5
	b) "Bicycle Boulevard" treatment	Speed management combined with traffic control changes to reduce the number of locations at which a bicyclist must stop.	



A.1 Bicycle accommodation dimensions

Bicycle lanes along an uncurbed roadway edge may be as narrow as 4'. Along curb and gutter, the minimum is 5' to provide pedal clearance from the curb, with an additional requirement of at least 3' of asphalt outside the gutter. Where parallel parking is present, the combined bike lane and parking area must be at least 12', and 13' is desirable for safe "door zone" clearance especially where there is substantial parking turnover.




Figure A.1: Typical Bicycle Lane Section – With and Without Parking

Sunnyvale's design minimums for lane widths are:

- 11' for travel lanes on arterials
- 10' for travel lanes on other streets
- 11' for center turn lanes (measured outside-to-outside), or 10' inside-to-inside

On streets without bike lanes, outside lanes at least 14' wide make it possible for motor vehicles to overtake bicycles without encroaching into the adjacent lane.




Figure A.2: Typical Bicycle Route Section (Wide Outside Lanes)

The following sections describe each toolkit option. As noted in Table A.1, Bicycle Plan Figures 5.1 through 5.7 show the streets for which each option is applicable.



A.2 Restriping

Restriping without travel lane removal

On some street segments, bike lanes can be added by narrowing lanes (subject to the City's minimum-width standards) without removing lanes. The City's goal is to extend bike lanes to the limit line or crosswalk, but where there is inadequate width to do so because of turn lanes or islands the bike lane can be dropped on the approach.

Travel lane removal

On streets with significant excess vehicle capacity, it may be possible to add bike lanes by removing one travel lane in each direction. Because a travel lane is roughly twice the width of a bike lane, removing two travel lanes can also enable the addition of a center turn lane or parking.

One specific type of travel lane removal, the "4 to 3 conversion", changes a street from four travel lanes (two in each direction) and no center turn lane, to two travel lanes (one in each direction) and a center turn lane, as shown in Figure A.3. In addition to being more comfortable for bicycling, the converted street is considerably safer for pedestrians to cross because the single travel lanes eliminate the "multiple-threat" collision mode in which a motorist in the near lane stops but hides a far-lane motorist who does not see the pedestrian. Pedestrian crossing safety can be further increased by adding median islands where needed, for example where a trail or a minor-street bike route crosses the busier street. Conversions to one travel lane per direction also increase safety by reducing excess speed, because they allow prudent drivers to set the pace.




Figure A.3: Adding bike lanes with a "4 to 3 conversion"



A.3 Parking modifications

Figure A.4 shows several options for adding bicycle lanes by removing or restricting parking on one or both sides of a street.




Figure A.4: Parking modification options for adding bike lanes

The 2000 Bicycle CIP proposed parking removal (sub-figure c) on streets where parking utilization was below 10% during both average daytime and nighttime periods. One-sided parking (b) was proposed where more than 60% of vehicles were parked on one side during the daytime. Daytime parking restrictions (d, e) were suggested as an option where daytime utilization was below 20% (residential) or 15% (workplace areas). This option is especially useful where there is no good alternative route for school (student) or work (adult) bicycle commuters.



A.4 Widening

On street segments where all travel lanes are needed and parking is either necessary or not present, adding bike lanes may require widening. Widening is "minor" if it can be accomplished within the existing right-of-way without utility relocations. "Major" widening requires property acquisition or removal of structures.

"Parking pockets" are a special case of minor widening where a landscape buffer strip is present and where parking demand is low but still high enough that parking removal is deemed infeasible. A parking pocket is a curb indentation into the landscape strip for one or more car lengths, enabling cars to be parked partly or fully behind the curb. This approach could be considered for the east side of Wolfe Road between Maria Avenue and Reed Avenue, a segment that currently has Shared Roadway Bicycle Markings.

Another special case of minor widening is the relocation of a median without modifying outside curb and gutter. Although this type of change is within the existing right of way, it may require relocation of utilities in the median. It may be possible to add bike lanes to parts of Mathilda Avenue between California Avenue and US-101 without modifying the outside curb and gutter, by removing parking from one side and shifting the median.

A.5 Shared Roadway Bicycle Marking

Bike lanes are the appropriate accommodation on streets where motor vehicles travel considerably faster than bicycles and traffic volume in the same or opposite direction makes safe passing difficult. On some streets where these conditions apply, constraints on available width or the difficulty of modifying parking may preclude the addition of bike lanes at least in the short term. This situation requires bicyclists to proactively ensure their safety by occupying enough of the available outside lane width to remain clear of parked cars whose doors might open, and of debris near the right edge of the roadway.

The Shared Roadway Bicycle Marking is now an approved traffic control device in California on streets with parallel parking. It is intended to show bicyclists how far from the right edge they should travel to avoid opening car doors, and to inform motorists that bicyclists will use the street and will stay clear of car doors for their safety. The approved marking consists of a bicycle icon and a double chevron as shown in Figures A.5 through A.7. Experimentation conducted in San Francisco found this marking superior to an earlier shape that enclosed the bicycle symbol in a hollow arrow, whose nickname ("sharrow") has come to be applied to the approved symbol as well. At the federal level this device is called the "Shared Lane Marking"; it has not yet been incorporated in the MUTCD.

Sunnyvale currently uses these markings on Wolfe Road between Maria Avenue and Reed Avenue, where daytime residential parking is relatively light but not deemed feasible to remove, in part because the long blocks on this segment mean that Wolfe Road resident and visitor parking cannot reasonably be shifted onto the relatively distant cross streets. However, the high vehicle speeds and low parking occupancy on that segment causes most cyclists to shift to the right in the long gaps between parked cars, forcing them to negotiate back out into traffic to pass the next parked car. Based on this experience, parking occupancy and speed differential should be considered when evaluating other street segments for Shared Roadway Bicycle Markings.





Figure A.5: Shared Roadway Bicycle Marking



Figure A.6: Marking in use




Figure A.7: Lateral placement of marking (centered 11' or more from curb face)

Before the Shared Roadway Bicycle Marking became available, Sunnyvale's practice for high-conflict narrow-outside-lane situations was to post "Share The Road" warning signs like the one shown in Figure A.8. Such signs were used on Sunnyvale Avenue between Evelyn Avenue and El Camino before that segment underwent a 4-to-3 lane reduction to reach its present layout. The 2003 Manual on Uniform Traffic Control Devices, which California has adopted as its Traffic Manual, has a "Share The Road" plaque (W16-1) for use with the W11-1 bicycle symbol sign as shown in Figure A.9.



Figure A.8: Sunnyvale "Share The Road" sign (from 2000 Bicycle CIP)



Figure A.9: MUTCD "Share The Road" sign assembly



Figure A.10: Experimental regulatory sign for narrow-lane situations



The intended meaning of "Share The Road" is "pass in the adjacent lane, when it is safe to do so". However, some motorists and bicyclists interpret it to mean "yield the lane so motor vehicles can pass without delay". This ambiguity limits the usefulness of the "Share The Road" message, even when augmented by graphics. Several jurisdictions around the U.S. are now experimenting with clearer regulatory messages for such situations, notably the "Bicycles May Use Full Lane" wording under consideration for a future MUTCD (Figure A.10). San Francisco uses "Bicycles Allowed Use Of Full Lane" signs in conjunction with Shared Roadway Bicycle Markings.

A.6 Speed Management

Overview

Bicycle lanes are inappropriate on streets with low traffic volumes. A bicycle lane's purpose is to facilitate overtaking of bicyclists by motorists where motor vehicles travel considerably faster than bicycles, and where traffic volume in the same or opposite direction makes overtaking difficulty or delay-prone.

On the residential and minor-collector streets that form several of Sunnyvale's "neighborhood" bike routes, traffic volumes are low enough that passing maneuvers can use the full width of the street, which is supported by the fact that these streets have either a dashed centerline or no centerline. On many such streets, daytime parking demand is sufficiently high that parking removal or daytime restriction may be infeasible.

The appropriate bicycle accommodation on such local streets is to deter speeding so that bicyclists – especially schoolchildren and parents riding with children – are comfortable sharing the street with motor traffic that can pass using the other half of the street. On some parts of neighborhood routes, turns or jogs every few blocks limit speeding, but additional measures may be needed on long straight segments without frequent stop signs. Deterring speeding on residential streets also benefits pedestrians, and reduces the attractiveness of the street for cut-through traffic.

Sunnyvale's Neighborhood Traffic Calming Program

Sunnyvale has a neighborhood traffic calming program consisting of two levels. The first level involves education and enforcement including radar speed signs; the second level adds engineering measures that physically limit the maximum speed of vehicles. Figure A.11 shows several examples: a neighborhood traffic circle that limits speeds to 12-15 mph at an intersection, a speed hump that limits speeding in the middle of a long block, and a median "gateway" island to prevent high-speed turns into a block. All of these measures including the circle are "bicycle-friendly"; traffic volumes are low enough that bicyclists can pass by the circle when no car is traversing it in the same direction.

Streets classified as arterials or collectors are not eligible for the traffic calming program. This is partly because vertical speed management devices such as speed humps and speed tables are not appropriate on higher-volume streets, and neighborhood traffic circles are not applicable above approximately 2,500 vehicles per day because of the need for large trucks to turn left in front of the island. "Gateway" islands as shown in Figure A.11(c) are considered to be on the neighborhood street, not the major street.





a) Neighborhood traffic circle, Canary Drive at Loch Lomond Court



b) Speed hump, Canary Drive between Inverness Way and Loch Lomond Court



c) "Gateway" island at start of block, Canary Drive at Inverness Way

Figure A.11: Neighborhood traffic calming devices in Sunnyvale

Bicycle Boulevards

A "bicycle boulevard" is a bicycle route using neighborhood or local streets on which stop signs have been largely shifted onto cross streets, enabling uninterrupted through bicycle travel. Because "turning" many stop signs in this way can attract through motor traffic to the route, it may be necessary to compensate with traffic calming devices or motor vehicle through-movement restrictions. The result is a preferential "throughway" for bicycles that retains full local access by motor vehicle to all parcels along the route.

In some cases the motor vehicle through-movement restriction may take the form of a natural barrier such as a creek or park, across which bicycles but not cars can travel. In



other cases the restriction is artificial, for example street closures or mandatory right-turn islands at collector- or arterial-street signals, with provision for bicycles to make the through movement at these locations.

Palo Alto's Bryant Street, the original Bicycle Boulevard, extends approximately three miles from south Palo Alto through downtown to the Menlo Park city limit. Its vehicular through movement restrictions consist of bicycle-and-pedestrian-only bridges across Adobe Creek and San Francisquito Creeks, two bicycle-permeable street closures, vehicle right turn islands at an arterial signal, and a neighborhood traffic circle. Bryant parallels Alma Street, an arterial roadway, and Middlefield Road, a major collector.

Bicycle boulevard candidates in Sunnyvale include The Dalles Avenue, the Alberta-Inverness route, the Evelyn-to-Tantau route described in the Bicycle Plan, Washington Avenue north of downtown, and possibly Morse Avenue between California Avenue and Ahwanee Avenue. The Sunnyvale / Maude / Borregas Avenue route to Moffett Park that will be created by the completion of the two freeway bicycle bridges will be another bicycle boulevard candidate because the bridges are gaps for motor traffic.



a) Bicycle-admitting street closure at Lowell Avenue



b) Bicycle- and pedestrian-only bridges at Adobe Creek



c) Bicycle-through / motor vehicle right-turn-only at Embarcadero

Figure A.12: Motor vehicle through-restrictions on Palo Alto's Bryant Bike Boulevard





Appendix B: Municipal Code Sections Relevant to Bicycling

B.1 Title 10: Vehicles and Traffic

Table B.1: Municipal Code - Chapter 10.56 Bicycles

Sections	Description (italics indicate paraphrased sections, [bracketed italics] are comments
10.56.020-10.56.120 (Bicycle licensing)	Bicycles must display a DMV-issued license sticker. The fee is \$3. Licenses are valid up to 3 years. Licenses must be affixed to license plates attached to the seat tube. Bicycles are inspected before being licensed, and are not licensed if not roadworthy. Licenses may be transferred when a bicycle is sold. Mutilating a bicycle's frame or license to prevent identification is unlawful. Licenses are required on rental bicycles. Bicycles believed to be stolen may be impounded for up to five days.
10.56.130. Equipment	Equipment required by California Vehicle Code section 21201 on bicycles operated on public highways is required in Sunnyvale for operation off public highways.
10.56.150. Riders— Seats—Number	Extends California Vehicle Code section 21204, which applies to riding on public highways, to riding anywhere in Sunnyvale.
10.56.140. Riding on sidewalks and overhead pedestrian crossings—Prohibited	 (a) Riding bicycles, motor driven cycles, and motor scooters is prohibited on sidewalks and also on overhead pedestrian crossings signed for pedestrian use only. Children under the age of thirteen years must walk their bicycles upon any overhead pedestrian crossing that is signed for pedestrian use only. (b) Sidewalk cycling is prohibited between ages 13 and 61. Children under 13 and adults over 61 may ride in single file on sidewalks except those adjacent to schools, stores, or other commercial buildings, exercising due care and yielding right of way to pedestrians. However, anyone regardless of age may ride on a sidewalk if riding in the adjacent street would be unsafe.
10.56.160 Speed	It is unlawful for any person to operate a bicycle on a street or highway at a speed greater than is reasonable or prudent having due regard for the traffic on, and the surface and width of, the street or highway, and in no event at a speed which endangers the safety of persons or property.
10.56.170 Stunt Riding	It is unlawful for any person riding or operating a bicycle to perform or attempt to perform any acrobatic or stunt riding upon any street or highway or other public place. This section is not meant to prohibit stunt riding as part of officially sanctioned events, or places clearly posting stunt riding as appropriate.
10.56.180. Emerging from alley or driveway	The operator of a bicycle emerging from an alley, driveway or building, upon approaching the sidewalk area extending across any alley or driveway, shall yield the right-of-way to all pedestrians approaching on the sidewalk or sidewalk area, and upon entering the roadway shall yield the right-of-way to all vehicles approaching on the roadway close enough to constitute a hazard
10.56.200. Towing, pulling or pushing persons or objects prohibited	It is unlawful for any person operating a bicycle to tow or pull any person or object from the rear thereof, except attachments specifically designed for this purpose, or push or propel any person or object in front of the bicycle.
10.56.210. Group riding.	It is unlawful for any persons operating bicycles upon a roadway to ride more than two abreast.
10.56.220. Parking	It is unlawful for any person to park, or allow to remain parked, any bicycle (1) upon any public street or roadway other than in such a manner that some portion of the bicycle touches the curb and so as to afford the least obstruction to vehicular traffic; or (2) upon any public sidewalk except in a bicycle rack, or against a building, or by means of a stand to maintain the bicycle in a vertical position, or at a curb, and in such a manner as to afford the least obstruction to pedestrian traffic.



Table B.1: Municipal Code – Chapter 10.56 Bicycles (continued)

10.56.230. Parking zones.	It is unlawful for any person to park, or allow to remain parked, any bicycle (1) upon any public street or roadway other than in such a manner that some portion of the bicycle touches the curb and so as to afford the least obstruction to vehicular traffic; or (2) upon any public sidewalk except in a bicycle rack, or against a building, or by means of a stand to maintain the bicycle in a vertical position, or at a curb, and in such a manner as to afford the least obstruction to pedestrian traffic.
10.56.240. Obedience to traffic control devices.	It is unlawful for any pedestrian or person operating a bicycle to disobey the directions of any traffic control device on public or private property unless otherwise directed to do so by a public safety officer or unless it is unsafe to do so at the time. A pedestrian walking a bicycle has all the rights and is subject to all of the regulations applicable to pedestrians.
10.56.250. Riding on school grounds and playgrounds.	It is unlawful for any person to ride or operate a bicycle in a reckless or irresponsible manner upon any playground or school ground where children are present.
10.56.260. Bicycle lanes, routes, and bikeways established.	The city council by resolution or motion may establish bicycle lanes and routes along designated streets or portions of streets. The city council by resolution or motion may establish bicycle paths in the interest of providing transportation, recreation and developing open space programs. The city council by resolution or motion may establish bikeways as defined in the Streets and Highways Code as the same exist or may be amended hereafter. Any person operating a bicycle along a bicycle route or Class III bikeway as defined in the Streets and Highways Code shall be subject to all of the rights and duties applicable to the operators of motor vehicles generally along the streets or portions of streets so designated, such designation being intended only to inform the operators of bicycles that such streets or portions of streets afford an expeditious route of travel by bicycle, and to alert the operators of motor vehicles of the likelihood of a higher incidence of bicycle traffic where the roadway is so marked.
10.56.270. Bicycle lanes, routes, paths, and bikeways—Signs and markings.	The city traffic engineer shall designate bicycle lanes, routes, paths and bikeways by the placement of appropriate signs and roadway markings.
10.56.280. Bicycle lanes—Class II bikeways—Use required and restricted.	When signs and markings are in place giving notice of the existence of any bicycle lane or Class II bikeway as defined in the Streets and Highways Code, it is unlawful for any person: (a) To operate a bicycle along any portion of the roadway of a street so designated other than within the bicycle lane or bikeway on the right side of the roadway, except for the purpose of passing another bicycle or to avoid an obstruction. (b) To operate any vehicle other than a bicycle along and within a bicycle lane or bikeway, except for the purpose of making a legal turning maneuver.



Table B.1: Municipal Code - Chapter 10.56 Bicycles (continued)

Table Bill Mailleipai	Code - Chapter 10.56 Bicycles (continued)
10.56.285. Bicycle paths—Class I bikeways—Use required and restricted.	When signs and markings are in place giving notice of the existence of any bicycle path or Class I bikeway established by this chapter, it is unlawful for any person: (a) To operate any unauthorized vehicle along any portion of the bicycle path or bikeway; (b) To operate a bicycle on the bicycle path or bikeway other than safely when passing pedestrians or bicyclists. This requirement does not prohibit a bicyclist from choosing to operate on a roadway when a Class 1 bikeway is available. (c) To operate a bicycle other than in a manner consistent with Section 9.62.040(h); (d) To fail to obey all signs and markings regulating use of the bicycle path or bikeway; (e) To operate a bicycle at all times in any manner other than with reasonable regard
	to the safety of all others, which shall include but not be limited to signaling all turns; passing to the left of any bicycle, authorized vehicle, or pedestrian being overtaken; and passing to the right of any oncoming bicycle, authorized vehicle or pedestrian.
10.56.286. Map showing bicycle facilities.	There shall be maintained on file in the department of public works and available for inspection by the public, a map showing the bicycle lanes, paths, routes, and bikeways, as established from time to time by the city council.
10.56.290. Provisions requiring Caltrans approval—Withdrawal of approval.	Any provision of this chapter which regulates bicycles, or delegates the regulation of bicycles upon the state highways or state freeways in any way for which the approval of Caltrans is required by law, shall cease to be operative six months after receipt by the city council of written notice of withdrawal of approval of Caltrans. Immediately upon the effective date of such revocation, the city clerk shall enter upon the original copy of the ordinance codified in this section a notification of such withdrawal.
10.56.300. Regulation of bicycles on state highways or freeways—Prior approval requirement.	Whenever this chapter delegates authority to a city officer, or authorizes action by the city council to regulate bicycles upon a state highway or a state freeway in any way which by law requires the prior approval of Caltrans, no such officer shall exercise such authority nor shall action by the city council be effective with respect to any state highway without the prior approval in writing of Caltrans when and to the extent required by Division 11 of the Vehicle Code.
10.56.310. Violation— Infraction.	Any person violating a provision of this chapter pertaining to licensing shall be subject to the maximum fine allowed under California Vehicle Code Section 39011. Any person violating any of the provisions set forth in this chapter pertaining to the operation of a bicycle or any provision of a resolution establishing a bicycle path, lane or bikeway authorized by this chapter shall be guilty of an infraction and upon conviction thereof shall be punished as set forth in Chapter 1.04 of this code.



B.2 Title 19: Zoning

The current Sunnyvale Zoning Code requires bicycle parking only for multifamily residences. However, the Code ties the provision of bicycle commuter support facilities (showers and/or dressing rooms) to the approvable Floor Area Ratio and required number of vehicle parking spaces of a proposed workplace development.

Table B.2: Municipal Code - Chapter 19 (Zoning) sections relating to bicycling

Chapter 19.12: Definitions			
19.12.030. "B"	(5) "Bicycle parking, secured" means bicycle parking facilities located in convenient, safe, clean and well-lighted areas, near building entrances, out of pedestrian paths, and within view of windows, security offices or high volumes of pedestrian traffic. Secured bicycle parking shall be protected from the weather and have surfaces that are mud, dust and debris free, and not be adjacent to car parking or traffic lanes without adequate protection. Secured bicycle parking devices shall include the following: lockers; or enclosed, locked limited access areas with rigid metal racks or fixed stationary objects which allow the bicycle frame and both wheels to be locked with a bicycle locking device or the bicyclist supplying a lock and six-foot cable. Secured bicycle parking shall be located in a flat area on the ground level. If located within a building, secured bicycle parking shall be easily accessible on the ground floor or by elevator to other floors. Reasonable and sufficient ingress and egress must be provided so that a bicycle may be easily moved in and out of the locker or locked limited access area.		
Chapter 19.32: Bu	ilding Heights, Lot Coverages, and Floor Area Ratios		
19.32.070. Floor area ratio (FAR).	(a) The total floor area ratio of all buildings on a parcel zoned M-S or M-3 and occupied in whole or in part by the following uses shall not exceed thirty-five percent: (b) The following are exceptions to the total floor area ratios set forth in (a): (5) Bicycle support facilities. When showers and/or dressing rooms are provided for use by bicycle commuters, the floor area occupied by such facilities may result in an increase in total floor area ratio of up to forty percent if approved through the miscellaneous plan permit process. Request for higher percentage substitutions shall be reviewed by the planning commission using the use permit process.		
Chapter 19.46: Of	Chapter 19.46: Off-Street Parking and Loading		
19.46.030. Preferential parking for car pool vehicles; bicycles.	(c) In lieu of up to five percent of required vehicle parking, secured bicycle parking may be allowed in industrial areas as follows: (1) Eight secured bicycle parking spaces for one vehicle space; or (2) One shower and dressing room with clothing lockers for bicycle commuters for two vehicle spaces; or (3) A combination of bicycle parking and showers/locker rooms. Up to five percent reduction of vehicle parking shall be considered through the miscellaneous plan permit process. Additional secured bicycle parking in lieu of vehicle parking shall be reviewed by the planning commission using the use permit process.		
19.46.050 Parking Standards	Table 19.46.050: Parking Requirements lists vehicle parking requirements and includes this Note (see 19.12.030 for definition of "secured bicycle parking) Note 1: Multifamily residential developments of five or more units shall have secured bicycle parking at a ratio of one secured bicycle parking space for every four units, but no fewer than four spaces.		
Chapter 19.88 Use Permits			
19.88.020 Authority	Authority for action on a use permit shall be vested as follows: (b) Major use permit determined by the planning commission for: (2) Floor area ratio which would otherwise meet the maximum of thirty-five percent except that floor area occupied by showers and/or dressing rooms provided for use by bicycle commuters increases the total floor area ratio over forty percent. This FAR bonus over thirty-five percent shall only be allowed for bicycle related facilities;		



Appendix C: Standard Operating Procedure: Bicycle and Pedestrian Safety Through Work Zones

The City of Sunnyvale sets forth rules and requirements for private and public construction activities in its Standard Operating Procedures (SOPs). The following two-page SOP and the subsequent figure address bicycle accommodation through work zones.

CITY OF SUNNYVALE

STANDARD OPERATING PROCEDURES BICYCLE AND PEDESTRIAN SAFETY THROUGH WORK ZONES

Warning sign types and locations:

- For any lane closures on the right side of the street there will be four required signs.
 - 1. Road Work Ahead
 - 2. Right /Bike Lane Closed Ahead (depending on the situation)
 - 3. A Bike Warning Sign either W-79, Share the Road, or Watch for Bicyclists. Staff prefers using the Watch for Bicyclists sign.
 - 4. Lane/Bike Lane Closed (depending on the situation)

Bike lane closures:

- For any bike lane closures there will be four signs required.
 - 1. Road Work Ahead
 - 2. Right /Bike Lane Closed Ahead (depending on the situation)
 - 3. A Bike Warning Sign either W-79, Share the Road, or Watch for Bicyclists. Staff prefers using the Watch for Bicyclists sign.
 - 4. Lane/Bike Lane Closed (depending on the situation)
- Staff will try to provide a 14 foot wide travel lane in situations where bicycles and cars will need to share a lane. If this is not achievable, the Caltrans minimum of 10 feet will be required.

Sidewalk closures:

- A clear pedestrian path will be provided through any sidewalk construction.
 - 1. This could be attained by
 - a) creating a pathway on the sidewalk around the construction, or through the parking strip
 - b) creating a coned or barricaded area off of the sidewalk,
 - c) designating a flagger to escort pedestrians safely through the work zones
 - 2. If there is no clear pathway immediately available, pedestrians will be detoured. Any detour will include detailed signage. The pedestrian will be notified of the detour before they reached the construction sites so that no backtracking would be required. Elaborate pedestrian detours will be avoided if possible because staff has found them to be ineffective.
- Issues concerning provisions for people with disabilities will be handled on a case by case basis.



City Of Sunnyvale Standard Operating Procedures (SOPs): Bicycle And Pedestrian Safety Through Work Zones, continued

Sign placement for work zones that will not be closing any travel lanes:

Work crews must warn roadway users of the work being conducted on the side of the roadway
even when no travel lanes are being closed. In this situation, the warning signs will be placed off
of the roadway as much as possible. Bicycle and pedestrian travel will be considered in the
placement of the sign. Sign visibility and proximity to the work zone will also be considered.

Duration of work:

• Work crews may use their discretion regarding warning signs and traffic control on jobs that will last under 1 hour. Short duration work is defined as work that occupies a location up to one hour. It is appropriate to use colored or marked vehicles with rotating strobe lights, arrow panels or truck mounted signs in place of advance signs and channelizing devices.

Nighttime visibility:

- Retro reflective 28" cones will be used to barricade work zones at night.
- Barricades with reflective striping will be used to hold warning signs.
- Arrow boards will be used under some circumstances.
- All work being conducted by the city at night will only done on an emergency basis.

Storage of Equipment on-street:

 No storage of construction equipment or debris is permitted on the street outside of working hours

Outside contractor compliance:

- Provide all encroachment permittees with a copy of the city's SOP.
 - 1. Make contractors aware ahead of time that they will be required to secure their own signs.
 - 2. Staff will continue to make announcements to sign vendors that the City will be requiring these signs.

Complaint procedures:

- For complaints related to work done by city crews, all complaints will be routed through the "field services" answer point.
- For complaints related to work done for capital projects or by contractors with encroachment permits, all complaints will be routed to the Project Administration division.






Figure C.1: Standard Operating Procedure for Right Lane and Bike Lane Closures



